

Calcite Neutralizer

Well water

Free reverse osmosis drinking system included

KEY SPECIFICATIONS

Water	Well water
Type	pH neutralizer (does not soften or filter chlorine)
Media	Natural calcite — crushed, screened calcium carbonate
Media tank (D × H)	12" × 52"
Recommended inlet pH	5.0 – 7.0
Control valve	BluePeak ProValve — ceramic disc
Connection size	1"
Bypass valve	1" full-flow, included
Backwash	Automatic, demand-initiated
Best suited to	Well water with low pH (acidic), blue-green staining
Service flow rate	12–14 GPM (12" tank)
Valve flow rate	Up to 28 GPM

OPERATING REQUIREMENTS

Operating pressure	30 – 125 PSI
Water temperature	40° – 110°F (4° – 43°C)
Electrical	120V / 60Hz — 12V transformer
Media replenishment	Calcite is consumed as it works — topped up periodically

COMPONENTS AND WARRANTY

Control valve	BluePeak ProValve — Hanksraft ceramic disc, assembled in Wisconsin, 72-hour memory backup
Mineral tank	Enpress fiberglass pressure tank — made in Ohio
Installation	Included — by a licensed North Carolina plumber
Drinking water	Free reverse osmosis drinking system included, installed at

WORTH BEING CLEAR ABOUT

- Raises pH of acidic water
- Reduces pipe corrosion & metal leaching
- Helps stop blue-green staining
- Adds calcium — hardness may rise
- A softener is often recommended downstream
- Does NOT remove iron, sulfur or chlorine

Installed by a licensed North Carolina plumber. Assembled in Texas.

(984) 401-9826

bluepeakwaterfiltration.com

Warranty: valve moving parts for as long as you own the home · electronics 5 years · media, RO and install 1 year · tanks per manufacturer. See bluepeakwaterfiltration.com/warranty