

Iron Breaker AIO XL (Dual Tank)

Well water · Best for 4+ bathrooms or 6+ people

Free reverse osmosis drinking system included

KEY SPECIFICATIONS

Best for	4+ bathrooms or 6+ people
Water	Well water
Configuration	Softening tank + Katalox Light tank + brine tank
Targets	Iron, manganese, hydrogen sulfide, hardness
Treatment method	Air-injection oxidation (AIO) — chemical-free
Softening capacity	Confirmed with your quote
Media tanks (D × H)	Two XL tanks, sizes confirmed with your quote
Brine / salt tank	Confirmed with your quote
Bypass valve	1" full-flow, included
Service flow rate	Confirmed with your quote
Valve flow rate	28 GPM

Not sure? We size it to how your family actually uses water.

OPERATING REQUIREMENTS

Operating pressure	30 – 125 PSI
Water temperature	40° – 110°F (4° – 43°C)
Electrical	120V / 60Hz — 12V 650mA transformer
Inlet turbidity	Under 5 FTU
Service flow	Confirmed with your quote

COMPONENTS AND WARRANTY

Control valves	BluePeak AIO ProValve — Hanksraft ceramic disc, air-injection oxidation, assembled in Wisconsin, 72-hour memory backup
Mineral tanks	Enpress fiberglass pressure tanks — made in Ohio
Softening resin	ResinTech CG10 strong-acid cation, 10% crosslinked — New Jersey, WQA Gold Seal

Backwash flow	Confirmed with your quote	Filter media	Katalox Light with Jacobi catalytic coconut-shell carbon
Regeneration	Upflow counter-current, demand-initiated metering	Installation	Included — by a licensed North Carolina plumber
		Drinking water	Free reverse osmosis drinking system included, installed at the kitchen sink

WHAT THIS SYSTEM TARGETS

- Iron (orange stains)
- Manganese (dark stains)
- Sulfur (rotten-egg odor)
- Hardness (scale)
- Sediment & turbidity
- Chlorine, taste & odor

Installed by a licensed North Carolina plumber. Assembled in Texas.

(984) 401-9826

bluepeakwaterfiltration.com

Warranty: valve moving parts for as long as you own the home · electronics 5 years · media, RO and install 1 year · tanks per manufacturer. See bluepeakwaterfiltration.com/warranty