

Softener Only

City or well water · Best for up to 3 bathrooms or 5 people

Free reverse osmosis drinking system included



KEY SPECIFICATIONS

Best for	up to 3 bathrooms or 5 people
Water	City or well water
Type	Softener only (no carbon — does not treat chlorine)
Softening capacity	48,000 grains
Resin volume	1.5 cu ft (about 75 lbs)
Media tank (D × H)	10" × 60"
Brine / salt tank	15" × 35" square
Connections	1" NPT elbows · 1.25" distributor tube
Bypass valve	1" full-flow, included
Optional pairing	Add a catalytic carbon tank for chlorine, taste and odor
Service flow rate	8–12 GPM (10" tank)
Valve flow rate	28 GPM

Not sure? We size it to how your family actually uses water.

OPERATING REQUIREMENTS

Operating pressure	30 – 125 PSI
Water temperature	40° – 110°F (4° – 43°C)

COMPONENTS AND WARRANTY

Control valve	BluePeak ProValve — Hanksraft ceramic disc, assembled in Wisconsin, 72-hour memory backup
Mineral tank	Enpress fiberglass pressure tank — made in Ohio

Electrical	120V / 60Hz — 12V 650mA transformer
Inlet turbidity	Under 5 FTU
Service flow	8–12 GPM (10" tank)
Regeneration	Upflow counter-current, demand-initiated metering

Softening resin	ResinTech CG10 strong-acid cation, 10% crosslinked — New Jersey, WQA Gold Seal
Installation	Included — by a licensed North Carolina plumber
Drinking water	Free reverse osmosis drinking system included, installed at the kitchen sink

WHAT THE SOFTENER REMOVES

- Hardness (calcium & magnesium)
- Scale on fixtures & appliances
- Soap scum & spotting
- Does NOT remove chlorine, iron or sulfur

Installed by a licensed North Carolina plumber. Assembled in Texas.

(984) 401-9826

bluepeakwaterfiltration.com

Warranty: valve moving parts for as long as you own the home · electronics 5 years · media, RO and install 1 year · tanks per manufacturer. See bluepeakwaterfiltration.com/warranty